

BACnet Thermostat – Modulating Heating and Cooling



FEATURES

- Energy Management System ready with BACnet communications
- Internal Sensor controls modulating fan and modulating SCR outputs
- Setpoints are Limited to internal settings (adjustable)
- Easy installation and operation
- Stand-alone operation
- Operates Fan Coil Units, Reheat Coils, and other modulating heating and cooling applications

SPECIFICATIONS

Model	EXL-01625
Fan Speeds	1
Cooling Outputs	2
Heating Outputs	2
Input Voltage	12-24 V AC/DC
Input Power	5 VA
Output Load Max	1.0 Amps
Relay Output	24 VAC/DC
Analog Output	0-10 VDC
Comm. Line	BACnet MS/TP

PART NUMBER:

EXL-01625 [Options]
Options
RA, DA, RN, TC

BACnet Thermostat

Description:

This BACnet thermostat operates any heating or cooling modulating application with 2 modulating cooling outputs and 2 modulating heating outputs. There are two analog outputs 0-10 Vdc and two PO/PC outputs for heating and cooling. Setpoints are adjustable from the BACnet interface. Space temperature setpoints are internally limited by a minimum and maximum setting (adjustable). The thermostat may be placed in the occupied or unoccupied mode. Space temperature is displayed under normal operation. The digital display indicates the current operating mode and outside air temperature (if provided via the BACnet interface).

The unoccupied mode may be overridden by an occupant adjustment up to the maximum allowed hours (adjustable). A manual timer allows from 0.1 to 99.9 hours of occupied operation and then returns to the unoccupied mode.

Heating and cooling stages are limited to maintain the discharge air temperature at no less than 50°F and no greater than 125°F with the optional discharge air sensor.

Night Setback modulates the heating or cooling when the room temperature is below 60°F or greater than 85°F and continues operation until the setpoint is exceeded by 5°F.

When ordering quantities greater than 30 customized setpoints and additional sequences are available at additional cost, please request a quote for your application.

Relay isolation allows for independent power supply on controlled equipment.

Options:

- ☐ RA Monitors Return Air Temperature for Troubleshooting.
- ☐ DA Monitors Discharge Air Temperature for Modulation.
- ☐ RN Remote Sensor - Allows the controller to be located in a secure room and the Room Sensor to be in an exterior zone.
- ☐ TC Time Clock - Provides an occupancy schedule.



BTL is a registered trademark of BTL. BTL is not responsible for the use of BTL products for purposes not intended by BTL. BTL is not responsible for the use of BTL products for purposes not intended by BTL. BTL is not responsible for the use of BTL products for purposes not intended by BTL.



HumeraTech is the exclusive U.S. distributor for ExactLogic products

14295 James Rd. Suite #200 | Rogers, MN | 55374

1-866-714-0522 | www.exactlogic.com