



FEATURES

- Energy Management System ready with BACnet communications
- Internal Sensor controls heating and cooling stages
- Setpoints are Limited to internal settings (adjustable)
- Anticycle time delays Protect equipment
- Easy installation and operation
- Stand-alone operation
- Operates Heat Pumps with 1 or 2 compressors
- Operates AC units with 1 to 2 cooling stages and 1 heating stage

SPECIFICATIONS

Model	EXL-01814
Fan Speeds	1
Cooling Outputs	2
Heating Outputs	1
Input Voltage	12-24 V AC/DC
Input Power	5 VA
Output Load Max	1.0 Amps
Digital Outputs	Relay - 24 VAC/DC
Analog Outputs	0-10 VDC
Comm. Line	BACnet MS/TP

PART NUMBER:

EXL-01814 [Options]

Options

RA, DA, RN

BACnet Thermostat

Description:

This BACnet thermostat operates in heating / cooling mode with 1 or 2 stages of cooling with 1 stage of heat or in heat pump mode with 1 or 2 compressors. All Setpoints are adjustable from the BACnet interface. Space temperature setpoints are internally limited by a minimum and maximum setting (adjustable). The thermostat may be placed in the occupied or unoccupied mode by a manual operator command or a timed override. Space temperature is displayed under normal operation. The digital display indicates the current operating mode, fan status, heating/cooling status, and outside air temperature (if provided via the BACnet interface).

The unoccupied mode may be overridden by an occupant adjustment up to the maximum allowed hours (adjustable). A manual timer allows from 0.1 to 99.9 hours of occupied operation and then returns to the unoccupied mode.

Heating and cooling stages are limited to maintain the discharge air temperature at no less than 50°F and no greater than 125°F, with the optional discharge air sensor.

Night Setback stages the heating or cooling when the room temperature is below 60°F or greater than 85°F and continues operation until the setpoint is exceeded by 5°F.

When ordering quantities greater than 30 customized setpoints and additional sequences are available at additional cost, please request a quote for your application.

Relay isolation allows for independent power supply on controlled equipment.

Options:

- RA Monitors Return Air Temperature for Troubleshooting.
- DA Monitors Discharge Air Temperature for Troubleshooting.
- RN Remote Sensor - Allows the controller to be located in a secure room and the Room Sensor to be in an exterior zone.
-



BACnet is a registered trademark of ASHRAE. EXACTLOGIC does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of these products to requirements of ASHRAE Standard 110 is the responsibility of the BACnet International. BTL is a registered trademark of the BTL Testing Laboratory.



HumeraTech is the exclusive U.S. distributor for ExactLogic products

14295 James Rd. Suite #200 | Rogers, MN | 55374

1-866-714-0522 | www.exactlogic.com