# **BACnet Airflow Measuring / Control Station-Totalization**





### **SPECIFICATIONS**

Model	EXL-01592
Damper Control	2 Modulating 2 Floating Point
Sensor Signal	Thermo Anemometer
Accuracy	± (5% + .2m/s)
Input Voltage	24 V AC/DC
Input Power	10 VA
Output Load Max	1.0 Amps
Digital Outputs	5 Relay - 24 VAC/DC
Analog Outputs	0-10 VDC
Comm. Line	BACnet MS/TP

## **PART NUMBER:**

EXL-01592 [Options]
Options
OA



#### **FEATURES**

- Energy Management System ready with BACnet communications
- Electronic Thermo Anemometer AirFlow Measurement Station (AFMS)
- Cubic Feet Per Minute (CFM) setpoint control (optional)
- Easy installation and operation
- **S**tand-alone operation
- Outside Air Temperature (OAT) measurement (optional)
- Outdoor Air Flow Measurement Station

### **BACnet Outside Airflow Measurement Station**

# **Description:**

This BACnet Airflow Measuring Station is designed to measure the airflow with four thermo anemometer sensors that are totaled from four individual CFM calculations for each sensor. The duct size and calibration factor for each of four ducts is entered and then the CFM is totaled.

The duct size in Cubic Feet (CF) and calibration factor are entered into BACnet Analog Value (AV) points.

The sensors measure from 30-4000 FPM standard, other ranges / accuracies are available.

The damper can be controlled to maintain the CFM setpoint using the Analog Output (AO) or floating point with 2 Binary Outputs (BO).

The CFM reading is displayed locally on the controller.

Mounting Brackets may be required.

When ordering quantities greater than 30 customized setpoints and additional sequences are available at additional cost, please request a quote for your application.

Relay isolation allows for independent power supply on controlled equipment.

#### **Options:**

☐ OA Outside Air Temperature OAT measurement

