

Meter – 1/2" Cold Water Register with 1 GPP output



FEATURES

- Multijet (inferential) impeller meter
- Meter is located in a strainer basket which allows for high amounts of impurities to be passed through the meter without affecting operation
- Installation in the vertical or horizontal position is acceptable
- Complies with AWWA C708 and ISO 4064 Class B Standards
- Factory tested and set calibration port
- Measures flows from 1 to 20 gallons per minute with a continuous flow not exceeding 15 gpm

SPECIFICATIONS

Series	EXL12011
Body	Epoxy Coated Bronze
Application	Domestic Cold Water
Standards	AWWA C708 & ISO 4064 Class B
Installation	Vertical or Horizontal
Media	Cold 40°F –122°F
Pressure Rating	150 PSI Maximum
Flow Rating	1-20 gpm
Continuous Flow	15 gpm
Indicators	.01, .1, 1, 10
Meter	5 position x100 10MGal

PART NUMBER:

EXL12011

Cold Water Meter

Description:

EXL12011 1/2" Cold Water Meter is designed for measurement of water flows of domestic or closed water systems flowing at a rate of 1 to 20 gallons per minute with a temperature from 40°F to 122°F.

The meter may be mounted in a vertical or horizontal position with the meter facing any direction.

The flow direction arrow indicates the direction of flow for the meter installation.

The meter reading is represented with a odometer style rolling number gage that indicates readings from 100 gallons to 9,999,900 gallons.

Individual dial gages indicate .01, .1, 1 and 10 gallons for visual indication of low flow rates down to a trickle.

Application:

- Living unit water consumption.
- Cooling Unit Chilled water consumption.
- Point of use sub-metering.
- Measuring gallons per minute for BTU consumption metering.

Options:

All EXL12011 Series Cold Water Meters come with a pulse output that is compatible with the ExactLogic product line of thermostats and controllers.